GUHRING



Hydraulic chucks

GÜHRING – YOUR WORLDWIDE PARTNER

Benefit from our **SuperLine** advantages:

common dimensions

- + optimal production conditions
- = cost benefits for customers with 100 % stock availability


Hydraulic chucks HSK-A

Product information

- HSK-A to ISO 12164-1 / DIN 69893-1
- axial length setting
- for tool shank tolerance h6
- balancing quality: G2.5 / 25,000 rev./min or U < 1 gmm

Scope of delivery

- incl. adjustment screw, article no. 4900
- incl. hexagon chuck key, article no. 4912
- order coolant supply set, article no. 4949, separately





Article no.	4662
Discount group	158

HSK	for shank Ø	d2	l1	12	incl. adjustment screw	SW	Weight	Order no.
d3	d1 h6 mm	mm	mm	mm	4900		kg	
HSK-A63	20	52.5	80	51	10.014	5	1.31	4662 20.063




ISO taper hydraulic chucks

Product information

- ISO taper to ISO 7388-1 form AD/AF
- axial length setting
- for tool shank tolerance h6
- \bullet balancing quality: G2.5 / 25,000 rev./min or U < 1 gmm

Scope of delivery

- incl. adjustment screw, article no. 4900
- incl. hexagon chuck key, article no. 4912
- order pull studs, article no. 4925 or 4926, separately





Article no.	4663
Discount group	158

ISO taper	for shank Ø	d2	l1	12	incl. adjustment screw	SW	Weight	Order no.
	d1 h6 mm	mm	mm	mm	4900		kg	
40	20	49.5	65	51	20.114	5	1.30	4663 20.040



Suitable reduction bushes can be obtained under article no. 4368 (sealed) or article no. 4369 (with peripheral cooling).

GÜHRING KG